

MEGABLAST

SPECIFICATION INFORMATION

MB1500 Series

Frame Features MB1500 series

- ▶ Fully welded product, no assembly required.
- ▶ Our frame design eliminates weight from being placed on the manifold and directs it to the lower frame and wheels.
- ▶ Wide stance ensures stability.
- ▶ Glove expanders keep gloves fully open thus reducing balling and promotes quicker, more efficient dry times.
- ▶ Blowers are fully covered to prevent water from making contact with the electric motor.
- ▶ Powder Coated.
- ▶ Heavy duty swivel casters are lockable for both wheel direction and rotation.

Electrical Features

- ▶ 120v standard power supply (220 volt is available).
- ▶ 495 cfm blower is thermally protected against overheating.
- ▶ 1250 watt Ceramic Strip heat element with stainless steel fins.
- ▶ Switches are conveniently located on the frame and all wiring is internal.
- ▶ Heat element is thermally protected against overheating by operating through a “High temperature cutoff switch) and cannot be operated without the fan in operation mode.

Electrical Certification

- ▶ This product meets or exceeds all requirements of electrical certification and is certified by the Electrical Safety Association (ESA Canada) and the Canadian Safety Standards (CSA).
- ▶ Meets and or exceeds NFPA requirements.

Warranty

- ▶ All MegaBlast Dryers have a full 2 year warranty on Electrical components, while the frame carries a full 5yr warranty against defects in materials and or workmanship.



JTEK
MANUFACTURING

SPECIFICATIONS

Model	Description	Capacity	Voltage	Amps	Watts	Db	CFM	Operating Temp.	Shipping Dims.
Glove & Boot Dryers									
MB1500P	Portable glove/boot	6 pair	120v	15	1500	60	214	+ 15	12 x 24 x 20"
MB1500GB	Glove/Boot	12 pair	120v	15	1500	60	490	+ 15	40w x 32"d x 82"h
MB1500GB	Glove/Boot	21 pair	120v	15	1500	60	490	+ 15	40w x 32"d x 82"h
MB3000GB	Glove/Boot	21 pair	120v	30	3000	60	980	+ 20	56w x 32"d x 82"h
Immersion / HAZMAT Suit Dryers (cold water rescue)									
MB1500G	Immersion/HAZMAT	2 Suit	120v	15	1500	60	490	+ 15	40"w x 32"d x 72"h
MB1500G-3	Immersion/HAZMAT	3 Suit	120v	15	1500	60	980	+ 15	56"w x 32"d x 72"h
MB1500G-4	Immersion/HAZMAT	4 Suit	120v	15	1500	60	490	+ 15	56"w x 32"d x 73"h
MB3000G	Immersion/HAZMAT	3 Suit	120v	30	3000	60	980	+ 20	56"w x 32"d x 73"h
MB3000G-4	Immersion/HAZMAT	4 Suit	120v	15	3000	60	980	+ 10	66"w x 32"d x 73"h
Turnout Gear Dryers									
MB1500FD	Turnout Gear	2 Suit	120v	15	1500	60	490	+ 20	40"w x 32"d x 82"h
MB1500FD-3	Turnout Gear	3 Suit	120v	15	1500	60	490	+ 10	56"w x 32"d x 82"h
MB1500FDD	Turnout Gear	4 Suit	120v	15	1500	60	490	+ 10	40"w x 32"d x 82"h
MB3000FDD	Turnout Gear	6 Suit	120v	30	3000	60	980	+ 10	56"w x 32"d x 82"h
MB3000FD-4	Turnout Gear	4 Suit	120v	30	3000	60	980	+ 20	56"w x 32"d x 82"h
MB3000FDD -8	Turnout Gear	8 Suit	120v	30	3000	60	980	+ 20	66"w x 32"d x 82"h
Combo Dryers									
MB1500C	1 Immersion/1 Turnout		120v	15	1500	60	490	+ 15	40"w x 32"d x 82"h
MB1500C-2	1 Immersion Suit / 2 Turnout Gear		120v	15	1500	60	490	+ 10	40"w x 32"d x 82"h
MB1500C-4	2 Immersion Suit / 2 Turnout Gear		120v	15	1500	60	490	+ 10	56"w x 32"d x 82"h
MB1500C-6	2 Immersion Suit / 4 Turnout Gear		120v	15	1500	60	490	+ 10	56"w x 32"d x 82"h
MB3000C-4	2 Immersion / 2 Turnout Gear		120v	30	3000	60	980	+ 20	66"w x 32"d x 82"h
MB3000C-6	2 Immersion / 4 Turnout Gear		120v	30	3000	60	980	+ 20	66"w x 32"d x 82"h